mk crochet.

Errata for Construction Vehicles Book



BULLDOZER

- Bulldozer Base should be stuffed with 1" thick cushion foam (not stabilizer foam)
- **Bulldozer Blade Sides** After completing Rows 1-26 of the blade center cut yarn and fasten often before cont on to row 1 of the blade sides,.
- Bulldozer Tracks Repeat rows 2-7 9 more times until you have 20 ridges



SKIDSTEER

• **Bucket** - missing attachment text at very end of pattern: "Sew ends of lift arms to the back of the completed bucket."



FLATBED TRUCK

- Front Fenders Close 6-st hole at end of fenders.
- *Window Section* leave a 60" tail when you've finished and fastened off on the odd number rows.
- **Double Wheel Well** fold back row 11 to row 8 (current printing says fold row 13 back to row 7 but there is no row 13. The rows end at 11.)



EXCAVATOR

- Cab side wall 2 (rejoin black from skein, not 'red'):
 - Row 4: Ch 1, sc 1, cut black leaving a 60" tail, change to white, sc 11, rejoin black from skein, sc 1 and turn. (13 sts)
- **Boom** remove an extra sc 1 from rnd 2 & rnd 7 to correct stitch count:
 - Rnd 2: Dc 2 in next st, dc 6, hdc 11, sc 1, sc 3 in next st, sc 11, sc 2 in next 4 sts, sc 9, sc2tog, hdc 9, dc 6, dc 2 in next 2 sts. (71 sts)
 - Rnd 7: Dc2tog, dc 6, hdc 11, sc 1, sc3tog, sc 11, sc2tog 4 times, sc 9, sc 2 in next st, hdc 9, dc 6, dc2tog 2 times. (63 sts)
- *Tracks* Repeat rows 2-7 9 more times until you have 20 ridges.



CRANE

• Tracks - Repeat rows **2-7** 11 more times until you have 24 ridges.